

VISUAL ALARM SOUNDER

SOUNDER without Flash

FEATURES

- ◆ 32 tones plus a selectable override tone
- ◆ Removable cover on deep base for surface wiring
- ◆ Independently certified to IP65
- ◆ Unique twist and lock bayonet mounting system
- ◆ Features base locking system as standard

Sound Level	Low	Med	High
Typical sound Output @ 1m (Tone 1) dB(A)	82.1	97.6	102.3
Current Consumption @24Vdc mA	8.3	16.4	30.8

Voltage range (Vdc): 21.6-28 Operating frequency (Hz): 440-2900Hz

Weight 0.22kg (shallow base) 0.25kg (deep base)

Temperature range: -20(°C) to +70(°C)



Model:SLC-16-L



Model: FS-102-S



Model: FS-152-SF



Model:SLC-13-L

SOUNDER without Flash

FEATURES

- ◆ 32 tones plus a selectable override tone
- ◆ Switch selectable beacon only feature
- ◆ Unique twist and lock bayonet mounting system
- ◆ Removable cover on deep base for surface wiring

Sound Level	Low	Med	High
Typical sound Output @ 1m (Tone 1) dB(A)	79.7	95.4	99.1
Current Consumption @24Vdc mA	10.8	19.9	34.4

Voltage range (Vdc): 21-28 Operating frequency (Hz): 440-2900Hz

Temperature range: -20(°C) to +70(°C)

Weight 0.22kg (shallow base) 0.25kg (deep base)